

FIBERGLASS ENCLOSURE DUPLEX BLOWER PACKAGES

Aquapoint positive displacement blower units may be housed in a common fiberglass enclosure to reduce footprint and cost for small applications requiring redundancy. Durable, light weight and easy to install, these enclosures are non-conductive and non-corrosive ensuring safe, long lasting blower operation. Fiberglass enclosures also provide exceptional weather protection and sound attenuation. The gel coat exterior is designed to resist ultraviolet degradation and will never crack, peel or require painting. A stainless steel support arm and locking hood allow for easy maintenance access. Choose from a variety of optional features to reduce noise, monitor component conditions and ensure efficient operation. Contact AquaPoint for application specific blower sizing and specifications.



STANDARD BLOWER PACKAGES

MODEL	BASE	BLOWER MODEL	MOTOR HP	DISCHARGE
APFB-1.5	FE02	URAI-22	1.5	1"
APFB-2	FE02	URAI-24	2	2"
APFB-3	FE02	URAI-24	3	2"
APFB-5	FE02	URAI-33	5	2"
APFB-7.5	FE02	URAI-33	7.5	2"

STANDARD FEATURES

- Weather Proof Fiberglass Enclosure
- Roots URAI Dual-Lobe Blower Blocks
- Premium Efficient ODP Motors
- Adjustable Motor Base
- Intake Filter / Silencer
- Dual V-Belt Drive System
- Check Valves
- Pressure Relief Valves
- Galvanized Steel Discharge Piping
- Flexible Discharge Connections
- Pressure Gauges
- Louvered Vent
- Ventilation Fan

OPTIONAL FEATURES

- Kaeser Tri-Lobe Blower Blocks for Sound Reduction
- Premium Efficient TEFC Motors
- Discharge Silencer (Field Installed)
- Temperature Gauges
- Filter Gauges
- Pressure Shut Off Switches
- Foam Insulation
- Heating Elements
- Additional Louvered Vents
- Stainless Steel Discharge Piping
- Integral VFD Controls

39 Tarkiln Place
New Bedford, MA 02745
T (508) 985-9050 | F (508) 985-9072

AQUAPOINT.COM